

IN THE CLAIMS

This listing of the claims will replace all prior versions, and listings, of the claims in this application.

1. (Currently Amended) A method, comprising:
generating validity information for a packet, wherein the validity information
comprises all necessary information required to perform a validity check of the
packet, the validity information comprising algorithm information to be used
to perform the validity check of the packet and algorithm initialization
information, the validity information further comprising public key
information of a sending node comprising an ~~identity of an entity~~address in a
database of a server from which the public key of the sending node can be
obtained, where no pre-established security association is needed to verify the
packet;

generating a packet header, comprising the validity information; and

sending the packet including the packet header from a first network node to a second
network node.
2. (Previously Presented) The method according to claim 1, wherein the generating of
the validity information comprises generating security information indicating security
services applied to the packet.
3. (Cancelled)

4. (Previously Presented) The method according to claim 1, wherein the generating of the algorithm information comprises generating the algorithm information which indicates an algorithm to be used to perform the validity check of the packet.

5.-10. (Cancelled).

11. (Previously Presented) The method according to claim 1, wherein the generating of the public key information comprises generating public key verification information indicating information in order to verify that the public key actually belongs to the sending node.

12. (Previously Presented) The method according to claim 1, wherein the generating of the validity information comprises generating an information item to prevent replay attacks.

13. (Previously Presented) The method according to claim 12, wherein the generating of the information item comprises including in the information item an indication of a procedure to be used for anti replay attacks.

14. (Previously Presented) The method according to claim 12, wherein the generating of the information item comprises including in the information item a time stamp.

15. (Previously Presented) The method according to claim 1, further comprising:
signing the packet using a private key corresponding to the public key indicated by the validity information.

16-17. (Cancelled)

18. (Currently Amended) An apparatus, comprising:
- validity information generating means for generating validity information for a packet;
 - packet header generating means for generating a header for the packet, comprising the validity information; and
 - sending means for sending the packet including the header to a receiving network node,
- wherein the validity information comprises all necessary information required for performing a validity check of the packet and no pre-established security association is needed to verify the packet, and the validity information comprises algorithm information to be used to perform the validity check of the packet, wherein the algorithm information comprises values to initialize an algorithm to be used to perform the validity check of the packet, the validity information further comprising public key information of a sending node comprising address in a database of a server~~an identity of an entity~~ from which the public key of the sending node can be obtained.

19.-41. (Cancelled)

42. (Currently Amended) An apparatus, comprising:
- a validity information generator configured to generate validity information for a packet;
 - a packet header generator configured to generate a header for the packet, comprising the validity information; and

a transmitter configured to send the packet including the header to a receiving network node,

wherein the validity information comprises all necessary information required to perform a validity check of the packet and no pre-established security association is needed to verify the packet, and the validity information comprises algorithm information to be used to perform the validity check of the packet, wherein the algorithm information comprises values to initialize an algorithm to be used to perform the validity check of the packet, the validity information further comprising public key information of a sending node comprising ~~an identity of an entity~~ address in a database of a server from which the public key of the sending node can be obtained.

43. (Previously Presented) The apparatus according to claim 42, wherein the validity information comprises security information indicating security services applied to the packet.

44.-49. (Cancelled)

50. (Previously Presented) The apparatus according to claim 42, wherein the public key information comprises public key verification information indicating information in order to verify that the public key actually belongs to the sending node.

51. (Previously Presented) The apparatus according to claim 42, wherein the validity information comprises an information item to prevent replay attacks.

52. (Previously Presented) The apparatus according to claim 51, wherein the information item to prevent replay attacks contains an indication of a procedure to be used for anti-replay attacks.
53. (Previously Presented) The apparatus according to claim 51, wherein the information item to prevent replay attacks contains a time stamp.
54. (Previously Presented) The apparatus according to claim 42, further comprising:
a signor configured to sign the packet using a private key corresponding to a public key indicated by the validity information in the packet header in the sending network node.
55. (Currently Amended) An apparatus, comprising:
a receiver configured to receive packets from a sending network node; and
a checker configured to perform a validity check of a packet by referring to validity information contained in a header of the packet,
wherein the validity information comprises all necessary information required to perform the validity check of the packet and no pre-established security association is needed to verify the packet, and the validity information comprises algorithm information to be used to perform the validity check of the packet, wherein the algorithm information comprises values to initialize an algorithm to be used to perform the validity check of the packet, the validity information further comprising public key information of a sending node comprising an address in a database of a server~~identity of an entity~~ from which the public key of the sending node can be obtained.

56. (Previously Presented) The apparatus according to claim 55, wherein the validity information comprises security information indicating security services applied to the packet.

57.-58. (Cancelled)

59. (Currently Amended) An apparatus, comprising:
a transmitter configured to forward packets from a sending network node to a receiving network node; and
a checker configured to perform a validity check of a packet by referring to validity information contained in a header of the packet,
wherein the validity information comprises all necessary information required to perform a validity check of the packet and no pre-established security association is needed to verify the packet, and the validity information comprises algorithm information to be used to perform the validity check of the packet, wherein the algorithm information comprises values to initialize an algorithm to be used to perform the validity check of the packet, the validity information further comprising public key information of a sending node comprising an address in a database of a server~~identity of an entity~~ from which the public key of the sending node can be obtained.

60. (Previously Presented) The apparatus according to claim 59, wherein the validity information comprises security information indicating security services applied to the packet.

61.-62. Cancelled.

63. (Currently Amended) A method, comprising:
receiving packets at a network node; and

performing a validity check of a packet by referring to validity information contained
in a header of the packet,

wherein the validity information comprises all necessary information required for
performing the validity check of the packet and no pre-established security
association is needed to verify the packet, the validity information comprising
algorithm information to be used for performing the validity check of the
packet, wherein the algorithm information comprises values to initialize an
algorithm to be used to perform the validity check of the packet, the validity
information further comprising public key information of a sending node
comprising an address in a database of a server entity from which the public
key of the sending node can be obtained.

64. (Currently Amended) A method, comprising:
forwarding received packets to a network node; and

performing a validity check of a packet by referring to validity information contained
in a header of the packet,

wherein the validity information comprises all necessary information required for
performing a validity check of the packet and no pre-established security
association is needed to verify the packet, the validity information comprising
algorithm information to be used for performing the validity check of the
packet, wherein the algorithm information comprises values to initialize an

algorithm to be used to perform the validity check of the packet, the validity information further comprising public key information of a sending node comprising an address in a database of a server~~entity~~ from which the public key of the sending node can be obtained.

65. (Cancelled)

66. (Currently Amended) A non-transitory computer readable storage medium ~~comprising with an executable~~ computer program stored thereon, wherein that when executed controls the computer program instructs a processor to perform:

generating validity information for a packet, wherein the validity information comprises all necessary information required to perform a validity check of the packet and no pre-established security association is needed to verify the packet, the validity information comprising algorithm information to be used to perform the validity check of the packet, wherein the algorithm information comprises values to initialize an algorithm to be used to perform the validity check of the packet, the validity information further comprising public key information of a sending node comprising an address in a database of a server~~entity~~ from which the public key of the sending node can be obtained;

generating a packet header, comprising the validity information; and

sending the packet including the header from a first network node to a second network node.

67. (Currently Amended) A non-transitory computer readable storage medium with comprising an executable computer program stored thereon, wherein that when executed controls the computer program instructs a processor to perform:

receiving packets at a network node; and

performing a validity check of a packet by referring to validity information contained in a header of the packet,

wherein the validity information comprises all necessary information required for performing the validity check of the packet and no pre-established security association is needed to verify the packet, the validity information comprising algorithm information to be used for performing the validity check of the packet, wherein the algorithm information comprises values to initialize an algorithm to be used to perform the validity check of the packet, the validity information further comprising public key information of a sending node comprising an address in a database of a server entity from which the public key of the sending node can be obtained.

68. (Currently Amended) A non-transitory computer readable storage medium comprising with an executable computer program stored thereon, wherein that when executed controls the computer program instructs a processor to perform:

forwarding received packets to a network node; and

performing a validity check of a packet by referring to validity information contained in a header of the packet,

wherein the validity information comprises all necessary information required for performing a validity check of the packet and no pre-established security association is needed to verify the packet, the validity information comprising algorithm information to be used for performing the validity check of the

packet, wherein the algorithm information comprises values to initialize an algorithm to be used to perform the validity check of the packet, the validity information further comprising public key information of a sending node comprising an address in a database of a server~~identity of an entity~~ from which the public key of the sending node can be obtained.